



SAE 2GR

Pratic SAE

EN The Pratic SAE/2 automatic espresso machine features: four programmable volumetric dosages of the water for coffee brewing from each group head, see-through water level glass, two multidirectional stainless steel steam wands and hot water tap for preparation of Americano and tea. It is also equipped with 2 independent semiautomatic override switches and an extractable heat exchanger.



SAE 2gr.



Pratic SAE 2

EN Features

- Built-in motor pump
- Automatic water refill (A.W.R.)
- Two stainless steel steam wands
- One hot water spout
- Rechargeable water softener
- Body made of baked enamel steel
- Frame structure is galvanized steel
- Boiler and pipes made in copper and brass
- Dual gauges for boiler and pump pressure control
- Indicator light to inform the machine is on
- Electrical cord length: 6 ft.

Equipment kit:

- 2 double & 1 single portafilter
- Blind filter
- Plastic tamper
- Spoon
- Connecting hoses
- 6" drain line
- 3/8 reducer

Color: black

Technical specifications

| | | SAE 2 |
|-------------------------------------|-----|------------------------------|
| Boiler capacity | qts | 12 |
| Heating element | W | 4000 |
| Total wattage | W | 4400 |
| Voltage | V | 208 VAC single phase minimum |
| Amps | A | 19.6 |
| Width | in | 28" |
| Depth | in | 21 1/2" |
| Height | in | 20 3/4" |
| Cup height - tray to group head | in | 5 3/4" |
| Net weight | lbs | 154 |
| Shipping weight with water softener | lbs | 202 |



Astoria espresso/cappuccino machines are "UL" listed for safety.



Astoria espresso/cappuccino machines are "ETL" listed for sanitation under "NSF-4" standards.



General Espresso Equipment Corporation

Supplier of the most complete line of espresso, cappuccino coffee machines, coffee grinders and accessories.

7912 Industrial Village Road - Greensboro, N.C. 27409

Tel. (336) 393-0224 - Fax (336) 393-0295

www.astoria.com - e-mail: info@geec.com

distributed by: